Nice

Nice

Nice, a world without limits.

Manufacturer of overhead door automation solutions

Niceforyou.com

Nice North America Corporate Office Carlsbad, Ca 92010 Tech: (760) 438 7000 Sales: (760) 438 7000 Toll Free: (800) 421 1587

Nice North America Door Division 1380 St-Regis Dorval, Quebec, Canada H9P-2T5 Tel: (514) 822 1116 Toll Free: (877) 888 1116

Phoenix Branch

1236 W. Southern Ave. Suite 104, Tempe, AZ USA Tel: (480) 557 0070 Toll Free (888) 816 8584

Commercial Door Operators



TROLLEY OPERATORS AND HORIZONTAL SLIDING DOOR OPERATORS

PRO-LT



Commercial Medium Duty Belt Drive Trolley Operator.

- High standing torque 1/2HP motor with thermal protection
- Heavy duty 4L V-belt and #41 roller chain and sprocket reductions
- · Permanently lubricated ball bearings on all drive shaft
- 1" output shaft on final drive
- · Adjustable friction clutch
- Emergency quick release disconnect for manual operation
- #410 roller chain drive and sprockets
- Magnetic solenoid brake (optional)
- UL325

PRO-T



Commercial / Industrial Continuous Duty Belt Drive Trolley Operator.

- Continuous duty industrial motor 1/2, 3/4 and 1HP
- · Full feature logic board controls
- Heavy duty 5L V-belt and #41 roller chain and sprocket reduction
- Permanently lubricated ball bearings on all drive shafts
- 1" output shaft on final drive
- Full overload protection
- Adjustable friction clutch
- Sliding door application and hardware (PRO-SD)
- Magnetic solenoid bake standard on PRO-TB and PRO-SD
- #410 roller chain drive on 1/2HP PRO-T and PRO-TB models
- #41 roller chain drive on all PRO-SD; 3/4, 1HP PRO-T and PRO-TB
- · Emergency quick release disconnect for manual operation
- UL325

JACKSHAFT OPERATORS

PRO-1461J



Limited duty jackshaft operator for high lift. vertical lift sectional doors.

- 1/2HP motor
- Absolute encoder
- Floor level disconnect
- Three button open/close/ stop push button station
- Integrated LED light
- Dry contact and light terminals
- Optional battery backup • Suitable for doors up to 14'
- and 850 lbs
- UL325

PRO-LJ // PRO-LH // PRO-LHA



Medium Duty belt drive jackshaft operator for High lift, vertical lift sectional doors and small rolling doors and grilles.

- Hight starting torque 1/2HP motor with thermal protection
- Heavy duty 4L V-belt and #41 roller chain and sprocket reductions
- Permanently lubricated ball bearings on all drive shafts
- 1" output shaft on final drive
- Adjustable friction clutch
- Left or right hand mounting (PRO-LH, PRO-LHA)
- Magnetic solenoid brake (std on PRO-LJ, PRO-LH, optional on PRO-LHA)
- Mechanical braking system (PRO-LHA)
- #41 roller chain drive and sprockets
- LJ incorporate a floor level disconnect, LH & LHA incorporate a floor level disconnect with emergency chain hoist, all with electrical cut-out switch
- UL325

PRO-J // PRO-H // PRO-HBH



Industrial, continuous duty belt drive jackshaft operator for high lift, vertical lift sectional doors. and rolling doors.

- Continuous duty industrial motor 1/2, 3/4 and 1HP
- Full feature logic boards controls
- Heavy duty 5L V-belt and #41 roller chain and sprocket reductions
- · Permanently lubricated ball bearings on all drive shafts
- 1" output shaft on final drive
- · Full overload protection
- Adjustable friction clutch
- Magnetic solenoid brake (std on PRO-HBH, optional for PRO-J, PRO-H)
- Mechanical braking system (PRO-J, PRO-H)
- #50 roller chain drive and sprockets
- J incorporates a floor level disconnect. H and HBH. incorporate a floor level disconnect with emergency chain hoist, all with electrical cut-out switch
- Left or right hand mounting (PRO-H, PRO-HBH)
- UL325



Medium duty gearhead iackshaft for small rolling doors, shutters and grilles.

- High starting torque 1/2HP motor with thermal protection
- Worm gear in oil bath reducer • #41 roller chain drive and
- sprockets
- Floor level disconnect or emergency manual operation
- Left and right hand mounting (must specify)
- UL325

(PRO-GHC) • Emergency chain hoist with electrical cut-out switch for manual operation

• Magnetic solenoid brake standard

• #50 roller chain drive and sprockets

• Full feature logic board controls

· Full overload protection

PRO-GH // PRO-GHC

- Universal left or right hand mounting.
- UL325





Commercial / Industrial Continuous Duty Belt Drive Apartment Trolley Operator.

- Continuous duty industrial motor 1/2 and 3/4HP
- Full feature logic boards controls
- · Full overload protection
- Adjustable friction clutch
- Magnetic solenoid brake (optional PRO-APTB)
- 3/4" and 1" pillow block bearings on pulley and drive shaft
- Heavy duty trolley idler c/w 41B12 sprocket
- Low profile 9" clearance design for apartment applications
- Timer to close and time delay on reverse standard
- Red and Green lights feature (optional)
- Quick disconnect trolley carriage
- UL325

PRO-GJ

PRO-GT // PRO-GSD



Commercial / Industrial Continuous Duty Worm Gear Trolley Operator.

- Continuous duty industrial motor 1/2, 3/4, 1, 1.5 and 2HP
- Full feature logic board controls
- Primary reduction worm gear speed reducer in oil bath, secondary reduction #41 roller chain and sprockets
- Permanently lubricated ball bearings on all drive shaft
- 1" output shaft on final drive
- Full overload protection
- · Adjustable in-line friction clutch
- Magnetic solenoid brake standard
- #41 roller chain drive
- Emergency quick release disconnect for manual operation
- Sliding door application and hardware (PRO-GSD)
- UI 325



Industrial, continuous duty worm gear drive jackshaft operator with chain hoist for large high lift, vertical lift sectional doors and rolling steel doors.

• Continuous duty industrial motor 1/2, 3/4, 1, 1.5, 2, 3 and 5HP (5HP available as PRO-GH only)

• Primary drive worm gear speed reducer in oil bath

Adjustable in-line friction clutch (Optional)

• Reinforced frame and cast iron pillow block bearings

PRO-EJ // PRO-EHJ



Industrial, duty belt drive jackshaft operator for rolling doors and grilles. Built-in mechanical load sensing feature and emergency egress.

- Continuous duty industrial motor 1/2 and 3/4HP
- · Permanently lubricated ball bearings o all drive shaft
- Built-in mechanical load sensing mechanism to eliminate jamming and damage to a locked rolling grille and door operator
- Emergency egress capability; floor level disconnect allows for opening a grille by manual operation or by door spring tension
- Emergency chain joist with floor level disconnect and electrical cut-out manual operation (EHJ)
- #50 roller chain drive and sprockets
- Heavy duty 5L V-belt and #41 roller chain and sprocket reduction
- · Full overload protection
- Adjustable friction clutch
- · Mechanical braking system
- Magnetic solenoid brake (Optional)
- UL325